

DUNSTAN STANDARD SPECIFICATIONS

CHASER BINS

	15T	18T	22T	26T	31T	39T	45T	60T
HEIGHT	3.7m	3.7m	3.61m	3.91m	3.91m	3.91m	3.91m	4.14m
WIDTH	3.5m	3.5m	3.5m	3.5m	3.5m	3.5m	3.5m	4.4m
LENGTH	5.22m	5.84m	7.64m	7.64m	9.2m	10.14m	TBC	12.83m
AUGER	16"	16"	20"	20"	20" or 24" Option	20" or 24" Option	24"	24"
DISCHARGE RATE (UP TO)	8T per minute	8T per minute	12T per minute	12T per minute	12T or 18T per minute	12T or 18T per minute	18T per minute	18T per minute
AXLE	Single	Single	Single	Single or Dual	Dual	Dual	Dual	Tri-Axle
STEERABLE AXLE	N/A	N/A	N/A	Option	Option	Option	Option	Standard
TYRES	30.5-32 18ply	30.5-32 x 18ply	30.5-32 x 18ply	30.5-32 x 18ply	30.5-32 x 18ply	30.5-32 x 18ply	800/65-32 x 20ply	800/65-32 x 20ply
BRAKES	Option	Option	Option	Option	Option	Option	Option	Standard
HYDRAULIC DRIVE	Option	Option	Option	Option	Option	Option	N/A	N/A
LOAD CELLS	Option	Option	Option	Option	Option	Option	Option	Option
INTERNAL FLOW CONTROL	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
ROLL TARP - HEAVY DUTY	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
PTO	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
FIRE EXTINGUISHER	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
ACCESS LADDER	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
WORK LIGHT (LED X2)	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
TAIL LIGHTS, FLASHING LIGHT, OVERSIZE SIGNAGE	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
INSPECTION WINDOW	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
PARKING JACK	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
PREMIUM PPG 2 PAC PAINT	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard



AUSTRALIAN MADE. WORLD CLASS.

Copyright © 2019 Dunstan, all rights reserved.